


Boss O-Rings




Materials: NBR
 Hardness: 90 shore
 Temperature Range:
 -25°C to 125°C (-13°F to 257°F)

Part Number	O-Ring ID	Wall Diameter
	in	
OB-02	0.239	0.064
OB-03	0.301	0.064
OB-04	0.351	0.072
OB-05	0.414	0.072
OB-06	0.468	0.078
OB-08	0.644	0.087
OB-10	0.755	0.097
OB-12	0.924	0.116
OB-14	1.048	0.116
OB-16	1.170	0.116
OB-20	1.475	0.118
OB-24	1.720	0.118
OB-32	2.337	0.118

*Also available in viton. Add suffix V. For example OB-06V

7


Face Seal O-Rings



Materials: NBR
 Hardness: 90 shore
 Temperature Range:
 -25°C to 125°C (-13°F to 257°F)

Part Number	O-Ring ID	Wall Diameter
	in	
OR-04	0.301	0.070
OR-06	0.364	0.070
OR-08	0.489	0.070
OR-10	0.614	0.070
OR-12	0.739	0.070
OR-16	0.926	0.070
OR-20	1.176	0.070
OR-24	1.489	0.070


Standard 61/62 O-Rings



Materials: NBR
 Hardness: 90 shore
 Temperature Range:
 -25°C to 125°C (-13°F to 257°F)

Part Number	O-Ring ID	WALL Diameter
	in	
OF-08	0.734	0.139
OF-12	0.984	0.139
OF-16	1.296	0.139
OF-20	1.484	0.139
OF-24	1.859	0.139
OF-32	2.234	0.139
OF-40	2.734	0.139
OF-48	3.359	0.139
OF-56	3.859	0.139
OF-64	4.359	0.139


High Pressure 61/62 O-Rings



Materials: Polyurethane
 Hardness: 90 shore
 Temperature Range:
 -40°C to 100°C (-40°F to 212°F)

Part Number	O-Ring ID	WALL Diameter
	in	
OO-08	0.734	0.139
OO-12	0.984	0.139
OO-16	1.296	0.139
OO-20	1.484	0.139
OO-24	1.859	0.139
OO-32	2.234	0.139

Cat® Flange D-Rings




Materials: NBR
 Hardness: 90 shore
 Temperature Range:
 -25°C to 125°C (-13°F to 257°F)

Part Number	D-Ring ID	WALL Diameter
	in	
OC-08	0.734	0.139
OC-12	0.984	0.139
OC-16	1.296	0.139
OC-20	1.484	0.139
OC-24	1.859	0.139
OC-32	2.234	0.139

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.


BSP Cone O-Rings - Crimp Couplings



Materials: NBR
 Hardness: 90 shore
 Temperature Range:
 -25°C to 125°C (-13°F to 257°F)

Part Number	BSP Dash Size	O-Ring ID	WALL Diameter
		in	
OBSP-04	-4	6.5	1.0
OBSP-06	-6	8.5	1.5
OBSP-08	-8	11.5	1.5
OBSP-10	-10	13	1.5
OBSP-12	-12	17	1.5
OBSP-16	-16	22	1.5
OBSP-20	-20	28.3	1.5
OBSP-24	-24	33.05	1.78
OBSP-32	-32	44.17	1.78


DKOL Cone O-Rings - Crimp Couplings



Materials: NBR
 Hardness: 90 shore
 Temperature Range:
 -25°C to 125°C (-13°F to 257°F)

Part Number	DKOL	O-Ring ID	WALL Diameter
		in	
OM-5X1	M12 x 1.5	5	1.0
OM-6X1.5	M14 x 1.5	6	1.5
OM-7.5X1.5	M16 x 1.5	7.5	1.5
OM-9X1.5	M18 x 1.5	9	1.5
OM-12X2	M22 x 2	12	2.0
OM-15X2	M26 x 2	15	2.0
OM-20X2	M30 x 2	20	2.0
OM-26X2	M36 x 2	26	2.0
OM-32X2.5	M45 x 2	32	2.5
OM-38X2.5	M52 x 2	38	2.5

DKOS Cone O-Rings - Crimp Couplings



Materials: NBR
 Hardness: 90 shore
 Temperature Range:
 -25°C to 125°C (-13°F to 257°F)

Part Number	DKOS	O-Ring ID	WALL Diameter
		in	
OM-5X1	M14 x 1.5	5	1.5
OM-6X1.5	M16 x 1.5	6	1.5
OM-7.5X1.5	M18 x 1.5	7.5	1.5
OM-9X1.5	M20 x 1.5	9	1.5
OM-10X2	M22 x 1.5	10	2.0
OM-12X2	M24 x 1.5	12	2.0
OM-16.3X2.4	M30 x 2	16.3	2.4
OM-20.3X2.4	M36 x 2	20.3	2.4
OM-26X2	M42 x 2	26	2.4
OM-32X2.5	M52 x 2	32	2.4

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT NOTICE.

O-Ring Kit



Part Number	Description
OK-10	O-Ring Boss Kit (212 pieces)
OK-20	O-Ring Face Seal Kit (155 pieces)
OK-30	SAE Flange O-Ring Kit (70 pieces)
OK-40	Caterpillar Flange O-Ring Kit (80 pieces)
OK-50	O-Ring Boss, Face Seal & Flange 61/62 Kit (260 pieces)
OK-60EB90	European Metric Standard O-Ring Kit (500 pieces)
OK-60JB90	Japanese Metric Standard O-Ring Kit (380 pieces)

These kits contain the most popular size 90 durometer nitrile O-rings, individually boxed, which will supply your shop, service truck, or parts counter with the size you need. Match the O-ring dash size to the dash size of the fitting.

Steel Cap/Plug Kit



Part Number	Description
PCDK-45	Domestic Cap & Plug Kit (148 pieces)

This kit contain the following:

- JIC Caps
- JIC Plugs
- ORFS Caps
- NPT Plugs
- MORB Plugs
- ORFS Plugs



Metric Thread ID Kit

Part Number	Cap and Plug Kits
MTK-31	Metric Thread ID Kit

Thread Identification Kits for male and female threads include:

- M8 x 1.0 through M52 x 2.0 metric thread gauges
- 1/8" BSPP through 2" BSPP thread gauges
- 31 dual threaded aluminum gauges

Velcro Straps



• For bundling two or more hoses together

Part Number	Length in
CGVS-19	19
CGVS-30	30