

Valves

Oil & Gas Industry Valves

JGB Enterprises, a full line supplier of high-performing industrial valves to its clients in the oil & gas industry including Butterfly Valves, Gate Valves, Check Valves, and more. Our relationships with national manufacturers and suppliers allow us to deliver the valves you need fast!

WAFER BUTTERFLY VALVE (Drop in Style)

ANSI 125/150 Flange Capable

Sizes: 2" - 12"
Pressure: 200 PSI NSCWP
Features: Short Neck, Notched Body, Pinless Disc, Lever or Gear Operated
Body Material: Ductile Iron, Epoxy Coated
Disc Materials: Ductile Iron Nickel Plated, Aluminum Bronze, Stainless Steel, Nylon Coated
Seat Materials: Buna, Viton
Stem: Available in Double D or Square Stem, 416 Stainless Steel



WAFER BUTTERFLY VALVE

ANSI 125/150 Flange Capable

Sizes: 2" - 24"
Pressure: 200 PSI NSCWP
Features: 4 Alignment Holes, Pinless Disc, Lever or Gear Operated
Body Material: Ductile Iron, Epoxy Coated
Disc Materials: Ductile Iron - Nickel Plated, Aluminum Bronze, Stainless Steel
Seat Materials: Buna, EPDM, Natural Rubber
Stem: Double D Style, 416 Stainless Steel



LUG STYLE BUTTERFLY VALVE

Sizes: 4" - 16"
Pressure: 200 PSI at ambient temperature (70°F)
Features: For use between two 150 lb. flanges. Will lock "open" or "closed"
Body Material: Ductile Iron, ASTM A536
Disc Materials: Aluminum bronze disc, ASTM B148, ALY.954
Seat Materials: Buna-N seal
Stem: Stainless steel top and bottom stems



CHECK VALVES

Sizes: 4" - 16"
Pressure: 4" - 12": 200 PSI @ 150 °F, 14" - 16": 150 PSI @ 150 °F
Features: Suitable for municipal and industrial applications
Body Material: Ductile Iron body with ASME Class 125 flanges
Disc Materials: Steel & fabric reinforced Buna-N
Cast Body Gasket: A536 60-45-12 Ductile Iron Lexide NK-511 (non-asbestos)



KNIFE GATE VALVES

- Conform to TAPPI TIS 405.8 face-to-face.
- Tested to MSS SP-81.
- Full Port.
- Full lug body drilled and tapped to ASME Class 150.
- Bi-Directional shut-off resilient seated design.

Sizes: 4" - 16"
Pressure: 150 PSI CWP



FLANGED GATE VALVE

Sizes: 2" - 16"
Pressure: 250 psi Non Shock CWP
Body Material: Cast Iron
Disc Materials: Cast Iron Wedge
Seat Materials: Buna-N seal
Stem: Bronze

Meets MSS SP-70, ASTM A126, AWWA C509, FM, and UL standards



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

JGB® Headquarters
 Liverpool, NY 13088
 (315) 451-2770

Buffalo Branch
 Cheektowaga, NY 14225
 (716) 684-8224

Southeast Hub
 Charlotte, NC 28273
 (704) 588-9920

St. Louis Branch
 St. Louis, MO 63111
 (314) 256-0833

Williston Branch
 Williston, ND 58801
 (701) 774-2195

Houston Branch
 Pasadena, TX 77503
 (281) 930-7777

Connect with us:



www.jgbhose.com